

CRF450X

Key Information

Category (ies)	Enduro
Price	99,999
Product Name	CRF450X

General

Service intervals	As per owners manual
0 -- 100 km/h (sec)	N/A

Dimensions & Weights

Claimed KERB weight (kg)	121
Length (mm)	2178
Width (mm)	821
Height (mm)	1273
Seat height (mm)	963
Rake/trail (°/ mm)	N/A
WheelBase (mm)	1480

Drive

Drive	Chain
Front suspension	47mm Showa inverted leading-axle twin-chamber cartridge-type telescopic fork with 16-step adjustable compression and rebound damping; 279mm axle travel
Rear suspension	Pro-Link with Showa damper, adjustable low-speed (13-step) & high-speed (3.5-turn) compression and 17-step rebound damping; 313mm axle travel

Engine

Tank capacity (l)	7.2
Starter	Electric/Primary kick
Fuel system	40mm Keihin FCR flat-slide carburettor
Engine configuration	Liquid-cooled 4-stroke 4-valve SOHC single
Cylinders	1
Valves Per cylinder	4
Capacity (cc)	449
Power (KW)	33.2KW / 7,500 RPM
Torque (NM)	43.1NM / 7,000 RPM

Gearbox	5-spd
---------	-------

Safety

Brakes	(f) 240x3mm hydraulic disc with dual-piston caliper and sintered metal pads (r) 240 x4mm hydraulic disc with single-piston caliper and sintered metal pads
--------	--

Styling

Frame material	Semi-double cradle; aluminium twin-spar
----------------	---

Wheels

Tyres (f)	90/90-21
Tyres (r)	140/80-18
Wheels	Aluminium rim/wire spoke